

## ICE- CREAM FREEZER -24°C ÷ -12°C

Freezer made with one-piece structure and internal and external made of AISI 304 stainless steel. Storage chamber equipped with shelf supports in AISI 304 stainless steel, 20 levels. Ventilated cooling system , evaporator positioned outside the refrigerating chamber. Hot gas defrosting. Control panel with electronic circuit board, HACCP alarms signaling. Equipped with 6 grids in AISI 304 stainless steel and 6 pairs of runners.



<i>Climate class</i>	5 (+40°C, 40% R.H.)	<i>Energy consumption E24, kW/h</i>	9,47
<i>Energy consumption/year, kW/h</i>	3457	<i>Energy Efficiency Class</i>	D
<i>Heavy duty cabinets</i>	This appliance is intended for use in ambient temperatures up to 40 °C	<i>LWA dB(A)</i>	62
<i>Net usable volume, lt</i>	580	<i>Refrigeration power -23,3°C W</i>	1054
<i>Volume, gross, lt</i>	682		

### Functional features

- Operating temperature: -24°C ÷ -12°C.
- Reliability tested up to + 43°C.
- Power unit with refrigerant fluid R452A.
- Control panel with electronic circuit board, HACCP alarm signaling: low and high temperature, black-out, core probe fails, high pressure and high condensation. Alarms are signalled by both visual and audio warnings; if chamber probe fails, the appliance continues operating on the basis of the mean compressor operating times prior to the malfunction. Operating temperature and relative humidity to 75% or 90% can be changed manually.
- Hyper Cold function for a rapid cooling of the chamber.
- Defrosting system by hot gas.
- Automatic condensation evaporation.
- Easy access to all controls and parts from the snap removable control board.
- Mechanical microswitch for internal fan stop and lamp switch on when door is open.

### Constructional features

- One-piece structure made of AISI 304 stainless steel, inner rounded corners, CFC-free expanded polyurethane insulation.
- Insulation thickness: 75 mm.
- Ventilated refrigeration system through finned evaporator with anti-corrosion treatment, positioned outside the refrigerating chamber means more storage space available.
- Rack bars in AISI 304 stainless steel, 20 levels, easily removable. Some examples of the inner capacity: 54 containers (36 x 16.5 x 12 cm), 150 mm clearance; 48 containers (36 x 16.5 x 12 cm), 180 mm clearance; 36 containers (36 x 25 x 12 cm), 150 mm clearance.
- Door on AISI 304 stainless steel hinges, easily reversible on site, equipped with a self-closing device for openings inferior to 90°. Integrated full-height handle with easy grip. Magnetic gasket, easily removable.
- Depth with door open: 1575 mm.
- Lighting through lamp with easy access.
- Key-operated lock.
- Stainless steel AISI 304 18-10 feet, adjustable in height from 105 to 155 mm.

### Standard equipment

- Equipped with 6 pairs of runners in AISI 304 stainless steel and 6 grids.

# AGL6B



## Optional

- Ice-cream containers, pairs of stainless steel guides, grids, printing terminal, temperature recorder, pedal door opening, swivelling wheels.

## Technical Data

<i>Working voltage</i>	230V 1N~ / 50Hz	<i>Net Weight</i>	145 kg
<i>Gross Weight</i>	160 kg	<i>Electric Power</i>	1,2 kW
<i>Dimensions</i>	75x94x204 cm	<i>Packing</i>	81x95x207 cm

Armadio frigorifero per gelateria  
ICE- CREAM FREEZER -24°C ÷ -12°C

