LCC Carina 02

es system k

EN | STANDARD FITTINGS

- integral condensing unit
- fan-assisted refrigeration
- double glazed front glass with screen printing, tilt forward
- double glazed side glass with screen printing
- double glazed rear doors, sliding (0,6 EXT, INT – hinged)
- three rows of glass shelves
- waterproof base shelf
- top LED lighting and illumination of each shelf
- electronic control panel
- electric defrost (1,0 and 1,4), natural defrost (0,6, EXT, INT)
- automatic condensate evaporation
- colour of profiles: gold or silver
- colour of screen printing: black, gold or silver
- wooden elements: toscany walnut, verona dark ash

PL | WYPOSAŻENIE STANDARDOWE

- agregat wbudowany
- chłodzenie dynamiczne
- szyba gięta zespolona pokryta sitodrukiem, uchylna
- szyby boczne zespolone pokryte sitodrukiem
- tylne drzwiczki zespolone, przesuwne (0,6 EXT, INT – uchylne)
- trzy rzędy półek szklanych
- blat ze sklejki wodoodpornej
- podświetlenie górne LED oraz każdej półki
- sterownik elektroniczny
- odmrażanie elektryczne (1,0 i 1,4), odmrażanie naturalne (0,6, EXT, INT)
- automatyczne odparowanie skroplin
- kolor profili: złoty lub srebrny
- kolor sitodruku: czarny, złoty lub srebrny
- elementy drewniane: orzech Toskania, jesion Werona ciemny

USE | DO UŻYTKU

DISPLAY | EKSPOZYCJA

ADVANTAGES | ZALETY

- lighting at the top and of each shelf
  oświetlenie górne i każdej półki
- customizable front panels
  dowolny wariant zabudowy frontowej
- temp. stability on each level
  temp. stała na każdym poziomie
- easy system of servicing and maintenance
  łatwa w eksploatacji i konserwacji





DIMENSIONS | WYMIARY



INT 45°



EXT 45°



SELF



CARINA 02	mm	dm³	❄	°C	⚡
INT 45		105	R290*	3H1 / +3 ÷ +8 3S / +11 ÷ +18	230 V/ 50 Hz
EXT 45		100	R290*	3H1 / +3 ÷ +8 3S / +11 ÷ +18	230 V/ 50 Hz
0,6	600	85	R290*	3H1 / +3 ÷ +8 3S / +11 ÷ +18	230 V/ 50 Hz
1,0	950	145	R290*	3H1 / +3 ÷ +8 3S / +11 ÷ +18	230 V/ 50 Hz
1,4	1450	235	R290*	3H1 / +3 ÷ +8 3S / +11 ÷ +18	230 V/ 50 Hz

* also available: R452A, R404A